

固定环 开口型

— 沉孔双孔固定型 —

Order 订货示例 **型式 (1Type · 2D)** — **3B**
RDQFHRQGU 30 — **12**

Type	材质	表面处理	附件
RDQFHRQGU	S45C	四氧化三铁保护膜	1个内六角螺栓
RDQFHRQGD		无电解镀锌	1个内六角螺栓 (SUS)
RDQFHRQGS	SUS304	—	—

型式	3B 选择		D1	P	d1	d2	M (粗牙螺纹)	d	H	t	C	X	(Z)	Y	(W)
	1Type	2D													
(沉孔双孔固定型) RDQFHRQGU RDQFHRQGD RDQFHRQGS	6	8	24	15	3.5	6.5	M3	3.4	6	3.3	0.5	8	8	4	1
		10					M4	4.5	7.5						
	8	8	25	17	4.5	8	M3	3.4	6	4.4	0.5	9	9	5	5
		10					M4	4.5	7.5						
	10	12	33	22	5.5	9.5	M5	5.5	9	5.4	0.5	10	11	5	5
		10					M4	4.5	7.5						
	12	12	35	24	5.5	9.5	M5	5.5	9	5.4	0.5	11	12	5	5
		15					M6	6.6	12						
	15	12	38	25	5.5	9.5	M5	5.5	9	5.4	0.5	13	13	6	5
		15					M6	6.6	12						
	16	10	36	26	4.5	8	M5	5.5	9	4.4	0.5	12	12	6	5
		12													
20	12	42	29	6.6	11	M6	6.6	12	6.5	0.5	13	13	8	5	
	15														6.5
25	12	48	37	5.5	9.5	M5	5.5	9	5.4	0.5	17	16	7	5	
	15														5.4
30	12	50	38	6.6	11	M6	6.6	12	6.5	0.5	18	17	10	5	
	15														6.5

交货期 报价确定

固定环 开口型

— 三孔固定型 / 三螺纹 (粗牙螺纹) 固定型 —

Order 订货示例 **型式 (1Type · 2D)** — **3B**
RDQFHRSGU 30 — **10**

Type	材质	表面处理	附件
三孔固定型 RDQFHRSGU	S45C	四氧化三铁保护膜	1个内六角螺栓
三螺纹固定型 RDQFHRSLU		无电解镀锌	1个内六角螺栓 (SUS)
RDQFHRSGD	SUS304	—	—
RDQFHRSLD		—	—

型式	3B 选择		D1	P	S	M1 (粗牙螺纹)	M (粗牙螺纹)	d	H	C	X	Y	(W)
	1Type	2D											
(三孔固定型) RDQFHRSGU RDQFHRSGD RDQFHRSGS	8	8	25	14	3.5	M3	M3	3.4	6	0.5	8	5	1.5
		10											
	12	8	30	22	5.5	M5	M4	4.5	7.5	0.5	10	5	1.5
		10											
	15	10	34	23	4.5	M4	M4	4.5	7.5	0.5	11.5	6	1.5
		15											
	16	12	35	26	5.5	M5	M5	5.5	9	0.5	12	6	1.5
		15											
	20	10	40	28	4.5	M4	M5	5.5	9	0.5	14	7	1.5
		12											
	25	15	45	34	6.6	M6	M6	6.6	12	0.5	15	8	1.5
		12											
30	15	50	38	6.6	M6	M6	6.6	12	1.0	20	10	1.5	
	15												1.0
40	15	60	48	6.6	M6	M6	6.6	12	1.0	23	12	1.5	
	18												1.0
40	18	70	56	9	M8	M8	9	14	1.0	26	13	2	
	18												1.0

①三孔固定型由于开口的相反侧(紧固部的相反侧)未进行开口加工, 紧固力比双孔固定型/双螺纹固定型小。
 ②在需要导向轴联接的保持力时, 建议使用双孔固定型/双螺纹固定型。

交货期 报价确定